DASHER



Hosted by A2Resource.com















VW Dasher 1974 Technical Specifications

Engine

No. of cylinders
Bore/stroke
Displacement
Compression ratio
Horsepower—SAE Net
Max. torque
Fuel regulrement

4 3.01/3.15 in. (76.5/80.0 mm) 89.7 cu. in. (1471 cc) 8.51 75 @ 5800 rpm 81 ft. lbs. @ 4000 rpm Regular, low-lead or lead-free

Engine Design

Engine block Cylinder head Valve train Cooling media, drive Cast from Aluminum alloy Spur-belt driven overhead cam Water, belt-driven pump, electr, radiator fan-thermostat contr. Downdraft carburetor w/automatic choke

Electrical System

Rated voltage Battery capacity Alternator Firing order

Fuel/air supply

12V 12V/54 amp/h Max. 770 W 1 - 3 - 4 - 2

Drive Train

Transmission Final drive

Clutch

4-speed synchro-tramaxle Front-wheel drive. Double-jointed drive axles.

Single disc, dry

Chassis and Suspension

Chassis Front suspension Unitized body/chassis, Bolt-on front fender, Independent front coil suspension struts, stabilizer bor.

Rear suspension Torsion crank axle with progressive coil springs, panhard rod for lateral stability.

Brakes and Wheels

Service brake

Power-assisted, dual diagonal hydraulic system. Self-adjusting discs up front. Mechanical, on rear wheels.

Emergency brake Rim size

Tire size Steering 5 J x 13, Rodial ply. 155 SR 13.

Rack and pinion, steering damper.

Dimensions and Weights

172.8 in. (4389 mm) Length 63.0 in. (1600 mm) Width 53.5 in. (1360 mm) Height (unloaded) 97.2 in, (2470 mm) Wheelbase 52.7 in. [1340 mm] Front track 52.5 in. (1335 mm) Rear track Ground clearance 4.7 in. (120 mm) 30.5 in. (775 mm) Overhang front 260 Ramp-angle front 37.2 in. (945 mm) Overhong rear 130 Ramp-angle rear 34.0 ft. (10.3 m) Turning circle

Performance Data

Top and cruising speed Fuel consumption (DIN 70030) 100 mph (160 km/h) 25 mpg erms volumented in America. Inc.
All specifications described in this cotolog are subject to change without notice.

33-30-46010

An additional policy covers major internal engine and transmission parts for 24 months or 24,000 miles, whichever comes first. See your dealer for details. VWoA warrants every new and factory rebuilt part and accessory distributed by YWoA and sold by authorized VW dealers in the U.S. and Canada to be free from defects under normal use for a period of 6 months or 6,000 miles, whichever comes first (excluding normal wear and tear, maintenance and service items). Any authorized VW dealer will replace or repoir defective parts free of charge including labor cost.

In addition, authorized VW dealers in the U.S. and Canada will guarantee their workmanship an all repairs for a period of 6 months or 6,000 miles, whichever comes first, excluding service, maintenance items and normal wear and tear. This workmanship guarantee is extended by the original servicing dealer who will arrange for corrective repairs. As a part of the VW Owner's Security Blanket, VW dealers will make every effort to provide qualified owners, by appointment, with substitute transportation without charge (subject to availability) whenever a new vehicle warranty repair cannot be completed on the day scheduled.

In this event, authorized VW dealers will provide to the owner of the car being repaired a courtesy vehicle for local use until the repair has been completed.