

*"Rules are for the interpretation of wise men  
and the obedience of fools"*



[Colin Chapman - Founder of Group Lotus Plc and Engineering Genius]

*Change the rules*



# Lotus Exige Technical Specifications


<b>Engine</b>	Mid-mounted, transverse, 1796cm <sup>3</sup> , 2ZZ-GE engine, Metal Matrix Composite (MMC) & aluminium lightweight and compact construction, 4 cylinders in line, water cooled, naturally aspirated with double overhead camshafts exploiting a Variable Valve Timing & Lift-intelligent (VVTL-i) system, rocker arms with low friction followers, 4 valves per cylinder, multi-point sequential fuel injection and electronic ignition.
<b>Engine management</b>	Lotus T4 engine control unit
<b>Max Power</b>	189 hp (192 PS) (141 kW) @ 7800 rpm
<b>Max Torque</b>	133 lbft (18.5 kgm) (181 Nm) @ 6800 rpm
<b>Maximum speed</b>	147 mph (237 km/h)
<b>0-60 mph</b>	4.9 s (0-100 mph 13.2 s) (0-100 km/h 5.2 s)
<b>Power to weight ratio</b>	216 hp/t (4.56 kg/PS) (6.21 kg/kW)
<b>Specific power output</b>	105 hp/l (107 PS/l) (78.5 kW/l)
<b>Emissions control</b>	Three-way catalytic converter. Euro IV emissions compliant with full On-Board Diagnostics (OBD).
<b>Transmission</b>	C64 Gearbox, aluminium lightweight construction, 6-speed, close ratio, constant mesh helical gears and open differential.
<b>Suspension</b>	Fully independent sport suspension utilising unequal length wishbones, Bilstein mono-tube gas damper, Eibach coaxial coil spring at each corner and front anti-roll bar.
<b>Chassis</b>	Lotus designed lightweight structure of epoxy bonded aluminium alloy extrusions with integral steel seat-belt support structure and lightweight steel rear subframe.
<b>Steering</b>	Solidly mounted mechanical rack and pinion steering box with 2.8 turns lock-to-lock.
<b>Brakes</b>	Track tuned 4-channel Anti-lock Braking System (ABS) with Lotus/AP-Racing twin-piston fixed aluminium alloy front brake calipers, Brembo single-piston sliding rear calipers and 282 mm diameter, 26 mm thick front and rear cast-iron ventilated and cross-drilled discs.

Power transmission	Emissions	Dimensions
Gear ratios	Fuel consumption	Luggage capacity 112 l - 50 kg
First 3.116 : 1	Urban 23.3 mpg 12.1 l /100 km	Wheelbase 2300 mm
Second 2.050 : 1	Extra urban 41.5 mpg 6.8 l /100 km	Track - front 1457 mm
Third 1.481 : 1	Combined 32.1 mpg 8.8 l /100 km	Track - rear 1507 mm
Fourth 1.166 : 1	CO <sub>2</sub> emissions 208 g/km	Overall length 3797 mm
Fifth 0.916 : 1	Fuel tank capacity 40 l	Overall width (door mirrors excluded) 1727 mm
Sixth 0.815 : 1		Overall width (door mirrors included) 1850 mm
Reverse 3.250 : 1		Overhang - front 1159 mm
Final drive 4.529 : 1		Overhang - rear 805 mm
		Weight distribution Front/Rear 692 mm
		Ground clearance - midladen (as per unladen with 2x75 kg occupants) 130 mm
		Vehicle mass - unladen (running order, full tank of fuel, no occupants, no luggage) 875 kg (no options) 916 kg (all options)

**Warranty:** Please refer to your dealer for manufacturer's warranty details (subject to terms and conditions).

Please refer to the price list for full details of optional equipment and pricing. Lotus reserves the right to change or amend specification and options at any time. All specifications and options are correct at time of going to press. To check specifications please contact your nearest official Lotus Cars dealer.

Standard features			
Interior		Exterior	
Interior Trim	Black Cloth	Body Colour	Ardent Red
Floor Covering	Black Carpet Mats		Saffron Yellow
Central Door Locking*	Standard		Old English White
Polished Aluminium Window Winders	Standard	Body Colour Door Mirrors	Standard
Face Level Air Vents	Standard	Front Mud Flaps	Standard
Lightweight Aluminium Footwell Divider	Standard	16-Spoke Lightweight Aluminium Alloy Wheels	Black
Leather Trimmed Sport Steering Wheel	Standard	Yokohama Advan A048 Tyres	Standard
Leather Trimmed Gear Lever Gaiter	Standard	Cross-drilled Brake Discs	Standard
Polished Aluminium Gearknob	Standard	ABS with Servo Assisted Brakes	Standard
Polished Aluminium Handbrake Sleeve	Standard	Sport Suspension (dampers and springs)	Standard
Four Speaker Audio Kit	Standard	3-Piece Rear Diffuser with Anodised Finish	Standard
Radio, CD-Player*	Standard		
Alarm and Immobiliser	Standard		
Auxiliary Front Driving Lamps	Standard		
MRSP £29995.00			
Cost options			
Air Conditioning†			
14-Spoke Lightweight Forged Aluminium Alloy Wheels with Ice Silver finish†			
Metallic Paint	Please refer to colour chart at back of brochure		
Custom Paint	Please refer to colour chart at back of brochure		
Extreme Paint	Please refer to colour chart at back of brochure		
Touring Pack**	Carpet set with lightweight aluminium passenger footrest, Black Alcantara interior, Electric windows, Leather sun visors, Interior stowage net, Blaupunkt Woodstock - DAB radio, CD-R/W compatible, MP3, MMC/SD card reader*		
Performance Pack***	Alcantara/Carbon effect sport seats with Exige logo, 4-point harnesses (track use only), Cross-bar, Acrylic capped door panels, Carbon effect door inserts, Twin oil coolers†		
†Non European Markets: Air conditioning and Oil coolers are fitted as standard equipment. Lightweight forged wheels form part of the optional Performance Pack. *Specifications may vary in Japan. **Cannot be specified with the Performance Pack. *** Cannot be specified with the Touring Pack.			

	
<b>Lotus Sport can offer the following track aftermarket accessories for the Exige</b>	
Safety	FIA approved 6-point roll cage, driver's seat and 6-point harness. Fire extinguisher and kill switch assemblies
Performance	Upated clutch assembly, Limited Slip Differential (LSD), Accusump oil control system
Handling	2-way adjustable suspension dampers, Adjustable front anti-roll bar
The above parts are for track use only and are not covered by the standard Manufacturer's vehicle warranty.	