







The Volkswagen Karmann Ghia. Beauty plus Sense.

Surely it's sensible to treat yourself to economy.

And economy you get-whether your desire runs to either

Couple or Convertible. The spirited V eldswagen engine is capable of

turning up a cruising speed of 70 m.p.b.—yet it can be run

at full throttle for miles and miles and still deliver

unparalleled gas economy. It's fun to drive a VW Karmann

Ghia. It's fun to get 32 miles to a gallon, too!

The large, velour-trimmed area in the rear is another feature of the VW Karmann Ghia.

And most practical, too. The foar-rubber upholstered bench serves as storage space or can seat two additional pastengers on occasion!



Very neat! A flick of the wrist and the rear storage space is doubled in size! And there's more room for additional packages under the front bood. Coupé or Convertible, every bit of space is sensibly put to good use.





The Volkswagen Karmann Ghia Convertible. She's a beauty! On sunny days with the top down ... sleek, low and racy. In bad weather the matching cover is removed—up goes the top and behold! All the comfort, quiet and protection of a closed automobile is yours. And how easily the fitted top goes up or down. One person ... one hand ... one minute! Even with the top up the new VW Karmann Ghia Convertible provides all 'round visibility ... an unusually large and low rear window ... large curved side windows ... narrow corner posts ... and a high, wide and handsome one-piece windshield. In every way, the Convertible has been designed and built with the same loving care that has made the Volkswagen Karmann Ghia Coupé a standard of beauty and quality.






The Volkswagen Karmann Ghia Convertible. Top up. Top down. Nobly styled. Mechanically delightful. For instance: the problem of how to open, push back and close the top quickly has been solved by a centrally-located

handle. It can be turned easily with one hand while you remain seated. Half the top folds into the body. And, in spite of its soundproof padding, the top lies flat and blends in with the striking lines of the body.


With their generous surface, the Karmann Ghia's powerful brakes react at the slightest pressure.



The wide, rubber-encased accelerator pedal is easy to control, whether you wear flat or high-heel shoes. Thick mats line the floor and the toe panel, too.



The whole inside is quickly warmed by the standard heater. A the four jets at the front, and the defroster jet at the rear, can be constant and correct temperature is assured by the fresh air ven-mixed with fresh air as required, even with the windows closed, tilators. The warm air from the engine which gently streams from and adjusted to enter from either the left or right hand side.




be comfortable. They rest on slanting runners and can be moved engine compartment can be locked from the justide of the

The seats have strong, durable upholstery. And they are individ- forward or back merely at the touch of a lever. The seat backs ually adjustable, so that no matter what size you are, you'll can also be adjusted easily to three convenient angles. Hood and



washer (standard equipment) Flexible, padded sun visors









4-cylinder, 4-stroke, O.H.V. type VW engine, rear-Engine

mounted.

Bore 3.031 in. (77 mm), stroke 2.520 in. (64 mm).

Displacement 72.740 cu.in. (1192 c.c.), 36 H.P. at 3700 R.P.M. S.A.E.

Compression ratio 6.6.

Carburetor Downdraft carburetor with accelerator pump. Cooling system Air cooling by fan, automatically controlled by

thermostat. Force-feed, oil cooler in air stream, Lubrication Transmission Synchromesh on 2nd, 3rd and 4th gears. Final drive

Power transmitted through spiral bevel gear and differential gear via two swing axle shafts to rear

wheels.

Chassis Front axle

Track

Tubular center section forked at rear with weldedon platform.

Independent suspension of wheels through upper and lower trailing arms: 2 laminated square torsion bars protected by tubes. Stabilizer.

Independent suspension of wheels through swing Rear axle axle shafts, trailing arms, one torsion bar on each side, mounted and protected in transverse tube.

Shock absorbers Front and rear: double-acting telescopic type. Footbrake Hydraulic type, operating on 4 wheels.

Wheelbase 94.5 in. (2400 mm). Turning circle 37 ft. approx. (11.25 m).

Front 51.4 in. (1305 mm), rear 50.7 in. (1288 mm).

Weights Overall

Performance

Climbing

ability

Tires

Unladen weight 1786 lbs. (810 kg), Max. load: 661 lbs. (300 kg), permiss, total weight 2447 lbs. (1110 kg).

Length 163.0 in. (4140 mm), width 64.3 in. (1634 mm). height 52.4 in. (1330 mm). dimensions

Fuel tank 10.6 U.S. gal. (40 liters) incl. 1.3 U.S. gal. reserve. capacity

32 miles per U.S. gal. (7.3 liters per 100 km). Max. and cruising speed 71 m.p.h. (115 k.p.h.).

1st gear 19° (34 %) 2nd gear 9.5° (17 %) 3rd gear 6° (10.5%) 4th gear 3° (5.5%)

5 tubeless large-section super balloon tires 5.60-15,

Outside mirror at extra cost

VOLKSWAGENWERK GMBH · WOLFSBURG · GERM

Presented by